

*SUPPLIERS OF AIR CONDITIONING—PLUMBING & HEATING—MECHANICAL PRODUCTS—
VENTILATION EQUIPMENT*

SUBJECT.....ALUMINIUM UNINSULATED FLEXIBLE DUCTING (TFF)

APPLICATION

TRADE SUPPLIES 'TFF' IS A RANGE OF FULLY FLEXIBLE UNINSULATED ALUMINIUM/POLYESTER LAMINATED DUCTING, WHICH HAS BEEN SPECIALLY DESIGNED FOR THE HVAC MARKET. BECAUSE OF ITS FLEXIBILITY IT IS EASY TO CONNECT TO EITHER ROUND OR OVAL DUCTING.



CONSTRUCTION

TRADE SUPPLIES 'TFF' IS A MULTI-PLY REINFORCED ALUMINIUM AND POLYESTER LAMINATED DUCTING WITH AN ENCAPSULATED HIGH TENSILE STEEL WIRE HELIX.

ADVANTAGES

- * SUPPLIED IN STANDARD 10 METER LENGTH, COMPRESSED TO 0.6 MTS.
- * INDIVIDUALLY BOXED.
- * EASY TO CONNECT TO EITHER ROUND OR OVAL DUCTING.
- * NO SPECIAL TOOLS REQUIRED FOR CUTTING OR FIXING.
- * IN THE EVENT OF FIRE NO TOXIC GASES ARE EMITTED.
- * THE PRODUCTS HAVE BEEN SUCCESSFULLY FIRE RESISTANCE TESTED TO BS476,PARTS 6, 7, AND 20.

TECHNICAL DATA

CONSTRUCTION MATERIAL.....REINFORCED ALUMINIUM/POLYESTER
WIRE PITCH..... 24MM
DIAMETER RANGE..... 80-610MM
TEMPERATURE RANGE..... -30/+140°C
MAXIMUM AIR VELOCITY..... 30 M/SEC
POSITIVE WORKING PRESSURE..2500 PA (MAX)
STANDARD LENGTH..... 10 METERS
PACKING..... INDIVIDUAL BOX OF 0.6 METERS
CLAMPING..... LIGHTENING BAND, STAINLESS STEEL
FLEX CLIPS.